

Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 40.6 mm, Rated cross-section: 4 mm², Colour: Black

RAL: 9005

Business data

Article number	3725.4	
Article name	ZQI 4/7 BK	
GTIN (EAN)	4044211111557	
Packaging unit	20	
Quantity unit	PC	
Weight per piece (not including packaging)	5 g	
Weight per piece (including packaging)	5.1 g	
Unit of weight	G	
Customs number	85389099	
Country of origin	CZ	
Prio-Article	3725.8	
Product description	Insulated cross-connector	

Data sheet 3725.4 ZQI 4/7 BK



Technical data

Dimensions		
Length	4.5 mm	
Width	40.6 mm	
Pitch size	6 mm	
Ratings		
Voltage with partition, max.	800 V	
Voltage without partition, max.	800 V	
Rated current	32 A	
Rated cross-section	4 mm ²	
Contamination degree	3	
Connection data		
No. of poles	7	
Materials		
Material	Copper alloy	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	\checkmark	
Touch protection is available	\checkmark	
Number of bridged terminals	7	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2022-06-10	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 3725.4 ZQI 4/7 BK

CONTACLIP

Media

Data sheet 3725.4 ZQI 4/7 BK



Accessories

##INVERSE##CONTA-CONNECT

	Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		
	<u>3515.2</u>	ZRK 4/2A BG	4044211151751	100		
	Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		
	1716.2	ZRK 4/2A Ex BG	4044211058579	100		
	Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		
	1717.2	ZRK 4/3A Ex BG	4044211058609	100		
	Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		
	3516.2	ZRK 4/3A BG	4044211151775	100		
	Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		
_	1718.2	ZRK 4/4A Ex BG	4044211058630	100		
	Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm ² , Width: 6.1 mm, Colour: Beige					
	Article number	Article name	GTIN (EAN)	Packaging unit		

3517.2

ZRK 4/4A BG

4044211151782

100