PRODUCT CS16925_STRADA-IP-8MX-DWC2-PC

STRADA-IP-8MX-DWC2-PC

Universal road lighting beam with excellent mixed illuminance and luminance uniformity. Typically IESNA Type II Medium. Variant made from PC.

SPECIFICATION:

Dimensions 90.0 x 90.0 mm Height 10.1 mm Fastening screw Ingress protection classes IP66, IP67 **ROHS** compliant yes 🕕



MATERIALS:


Component **Type** Material Colour **Finish** PC STRADA-IP-8MX-DWC2-PC Multi-lens clear STRADA-IP-8MX-SEAL Silicone Seal clear

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CS16925_STRADA-IP-8MX-DWC2-PC	Multi-lens	156	52	52	6.7
» Box size: 480 x 280 x 300 mm					

PRODUCT DATASHEET

CS16925_STRADA-IP-8MX-DWC2-PC



See also our general installation guide: www.ledil.com/installation_guide

PRODUCT DATASHEET


CS16925_STRADA-IP-8MX-DWC2-PC

OPTICAL RESULTS (MEASURED):



LED LUXEON 5050 Round LES


FWHM / FWTM Asymmetric Efficiency 90 % Peak intensity 0.5 cd/lm LEDs/each optic Light colour White Required components:



LUMILEDS

LED LUXEON 5050 Square LES


FWHM / FWTM Asymmetric Efficiency 90 % Peak intensity 0.5 cd/lm LEDs/each optic 1 White Light colour Required components:



LUMILEDS

LED LUXEON 5050 Square LES


 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ Asymmetric Efficiency 90 % Peak intensity 0.5 cd/lm LEDs/each optic Light colour White Required components:



LUMILEDS

LED LUXEON 5050 Square LES

FWHM / FWTM Asymmetric Efficiency 89 % Peak intensity 0.4 cd/lm LEDs/each optic White Light colour Required components:



PRODUCT DATASHEET


CS16925_STRADA-IP-8MX-DWC2-PC

OPTICAL RESULTS (MEASURED):




LED LUXEON 5050 Square LES

FWHM / FWTM Asymmetric
Efficiency 89 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



WNICHIA


LED NV4WB35AM
FWHM / FWTM Asymmetric
Efficiency 88 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):




LED XHP35 HI
FWHM / FWTM Asymmetric
Efficiency 87 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White



CREE - LED


Required components:

LED XP-L2
FWHM / FWTM Asymmetric
Efficiency 84 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



DESCRIPTION LUMILEDS

LED LUXEON 7070
FWHM / FWTM Asymmetric
Efficiency 84 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White




WNICHIA

Required components:

LED NFMW48xA

FWHM / FWTM 57.0 + 148.0° / 108.0 + 160.0°


Efficiency %
Peak intensity 0.5 cd/lm
LEDs/each optic 8
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):



LED NVSxE21A FWHM / FWTM Asymmetric Efficiency 84 % Peak intensity 0.4 cd/lm LEDs/each optic Light colour White Required components:




OSRAM

LED Duris S8


FWHM / FWTM 57.0 + 148.0° / 108.0 + 160.0°

Efficiency % Peak intensity 0.5 cd/lm LEDs/each optic 8 White Light colour Required components:




OSRAM Opto Semiconductors

LED Duris S8 FWHM / FWTM Asymmetric Efficiency 86 % Peak intensity 0.4 cd/lm LEDs/each optic 1 Light colour White Required components:



SAMSUNG

LM28xB Series FWHM / FWTM Asymmetric Efficiency 88 % Peak intensity 0.8 cd/lm LEDs/each optic White Light colour Required components:



OPTICAL RESULTS (SIMULATED):



LED

SEOUL DC 5050 6V

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$

 $58.0 + 146.0^{\circ} / 114.0 + 155.0^{\circ}$

Efficiency Peak intensity


0.6 cd/lm

LEDs/each optic

White

Light colour

Required components:



PRODUCT DATASHEET

CS16925_STRADA-IP-8MX-DWC2-PC

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

8/8

www.ledil.com/ where_to_buy