



Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 14.2 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: natural

	Bu	Isin	ess	data
--	----	------	-----	------

Article number	<u>2423.0</u>	
Article name	Q 3	
GTIN (EAN)	4044211052058	
Packaging unit	50	
Quantity unit	PC	
Weight per piece (not including packaging)	2.42 g	
Weight per piece (including packaging)	2.46 g	
Unit of weight	G	
Customs number	85389099	
Country of origin	CZ	
Product description	Cross-connector	
Colour	Natural	



### **Technical data**

Dimensions	
Length	4 mm
Width	14.2 mm
Hole height	2.5 mm
Hole diameter	2.8 mm
Hole spacing (mid-point to mid-point)	5.1 mm
Pitch size	5 mm
Slotted hole	$\checkmark$
Ratings	
Voltage with partition, max.	400 V
Voltage without partition, max.	400 V
Rated current	20 A
Rated cross-section	2.5 mm <sup>2</sup>
Contamination degree	3
Connection data	
No. of poles	3
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm
Materials	
Material	Copper
Surface	Tin-plated
Surface screw	Galvanized
Further technical data	
Mounting type	Screwable
Number of bridged terminals	3



### **Technical data**

Environmental Product Compliance		
REACH Conform	No	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
REACH CAS 1 Substance	LEAD	
REACH CAS 1 Percent minimal	0.1 %	
REACH CAS 1 Percent maximum	4 %	
REACH CAS 1 Number	7439-92-1	
RoHS Conform	yes	
RoHS Exception rule	6c	

#### Media







#### Accessories

#### Screwdriver

	Screwdriver with bare blade, Colour: Black-grey			
- Conneur	Article number	Article name	GTIN (EAN)	Packaging unit
	1086.0	SDB 0,6x3,5	4044211014797	1 ST