

VIEW ON MATING SIDE

∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	∞	

A = 32 CONTACTS L=4,5

Marking	Standard
Performance level	GI/O = Contact area level / Termination fin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85040-0002 sht.1
Technical Data	PS-85042-0001

A	GI/O	a1-l6	b1-l6
Contact symbol	Perform. level	Contact position number	

ECN MG 1998-2554 first release	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	REVISIONS	DATE	BY	REASON
△	LTR	MM	IN.	IN.
DESIGN DIMENSION		<input type="checkbox"/> MM	<input type="checkbox"/> IN.	
EQUIVALENT DIMENSION		<input type="checkbox"/> MM	<input type="checkbox"/> IN.	
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				
3 PLACE ± .		±		
2 PLACE ± .		±		
1 PLACE ± .		±		
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2°				
INCH METRIC				
DRWG BY	KN	SIGN		
CHK'D BY	Ca	SIGN		
APP'D BY	JB	SIGN		
SCALE				
CAD/CAM PROJECT NAME		S8504007 s11		
REVISE ONLY ON CAD SYSTEM		SH.	REV.	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
TITLE		32 pos. female connector acc. DIN 41612 style B/2 contacts arrangement		
PART NO.		SD-85040-0713		
DWG NO.		SD-85040-0713		
SHEET NO.		1 OF 1		
DATE		97/07/30		
MOLEX EUROPE		SIZE A		