



Position switch Metal enclosure 40 mm according to EN 50041 Device connection 1x (M20 x 1.5) 1 NO/1 NC quick action contacts Rotary actuator right/left adjustable, rod lever made of plastic 200 mm long

|  |   |
|--|---|
| <b>product brand name</b>  | SIRIUS  |
| <b>product designation</b>   | Mechanical position switches  |
| <b>product type designation</b>  | 3SE5  |
| <b>manufacturer's article number</b>   |   |
| <ul style="list-style-type: none"> <li>• of the supplied basic switch</li> <li>• of the supplied actuator head for position switches</li> <li>• of the supplied operating lever</li> <li>• of the supplied switching contacts</li> <li>• of the supplied empty enclosure with cover</li> </ul> | <a href="#">3SE5112-0CA00</a><br><a href="#">3SE5000-0AH00</a><br><a href="#">3SE5000-0AA82</a><br><a href="#">3SE5000-0CA00</a><br><a href="#">3SE5112-0AA00</a> |
| suitability for use safety switch  | No  |
| <b>General technical data</b>  |   |
| product function positive opening  | No  |
| insulation voltage rated value   | 400 V   |
| <b>degree of pollution</b>   | class 3   |
| <b>surge voltage resistance rated value</b>  | 6 kV  |
| <b>protection class IP</b>   | IP65/IP67   |
| <b>shock resistance</b>  |   |
| <ul style="list-style-type: none"> <li>• according to IEC 60068-2-27</li> </ul>  | 30g / 11 ms   |
| vibration resistance according to IEC 60068-2-6  | 0.35 mm/5g  |
| mechanical service life (switching cycles) typical   | 15 000 000  |
| electrical endurance (switching cycles) at AC-15 at 230 V typical  | 100 000   |
| <b>electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical</b>   | 10 000 000  |
| <b>Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026</b>   | 6 000   |
| <b>thermal current</b>   | 10 A  |
| <b>material of the enclosure of the switch head</b>  | plastic   |
| <b>reference code according to IEC 81346-2</b>   | B   |
| <b>continuous current of the C characteristic MCB</b>  | 1 A; for a short-circuit current smaller than 400 A   |
| <b>continuous current of the quick DIAZED fuse link</b>  | 10 A; for a short-circuit current smaller than 400 A  |
| <b>continuous current of the DIAZED fuse link gG</b>   | 6 A   |
| <b>active principle</b>  | mechanical  |
| <b>repeat accuracy</b>   | 0.05 mm   |
| <b>Substance Prohibitance (Date)</b>   | 07/01/2006  |
| <b>minimum actuating torque in directions of actuation</b>   | 0.25 N·m  |
| <b>length of the sensor</b>  | 281 mm  |
| <b>width of the sensor</b>   | 40 mm   |
| <b>design of the switching contact</b>   | mechanical  |

|  |   |
|--|---|
| <b>operating frequency rated value</b>                   | 50 ... 60 Hz  |
| <b>number of NC contacts for auxiliary contacts</b>      | 1   |
| <b>number of NO contacts for auxiliary contacts</b>      | 1   |
| <b>operational current at AC-15</b>                      |   |
| • at 24 V rated value                                    | 6 A   |
| • at 125 V rated value                                   | 6 A   |
| • at 240 V rated value                                   | 6 A   |
| • at 400 V rated value                                   | 4 A   |
| <b>operational current at DC-13</b>                      |   |
| • at 24 V rated value                                    | 3 A   |
| • at 125 V rated value                                   | 0.55 A  |
| • at 250 V rated value                                   | 0.27 A  |
| • at 400 V rated value                                   | 0.12 A  |
| design of the interface for safety-related communication | without   |
| <b>Enclosure</b>   |   |
| <b>design of the housing</b>                             | block, narrow   |
| <b>material of the enclosure</b>                         | metal   |
| <b>coating of the enclosure</b>                          | cathodic dip coating  |
| <b>design of the housing according to standard</b>       | Yes   |
| <b>Drive Head</b>  |   |
| <b>design of the actuating element</b>                   | Twist actuator, plastic rod, length 200 mm                            |
| <b>standard-compliant actuator head</b>                  | EN 50041, design D  |
| <b>shape of the switch head</b>                          | roller  |
| <b>circuit principle</b>                                 | snap-action contacts  |
| number of switching contacts safety-related              | 0   |
| <b>Connections/ Terminals</b>                            |   |
| <b>type of electrical connection</b>                     | screw-type terminals  |
| <b>type of connectable conductor cross-sections</b>      |   |
| • solid  | 1x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.5 ... 0.75 mm <sup>2</sup> ) |
| • finely stranded with core end processing               | 1x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.5 ... 0.75 mm <sup>2</sup> ) |
| • at AWG cables solid                                    | 1x (20 ... 16), 2x (20 ... 18)  |
| • at AWG cables stranded                                 | 1x (20 ... 16), 2x (20 ... 18)  |
| <b>cable entry type</b>                                  | 1x (M20 x 1.5)  |
| <b>Communication/ Protocol</b>                           |   |
| <b>design of the interface</b>                           | without   |
| <b>Ambient conditions</b>                                |   |
| <b>ambient temperature</b>                               |   |
| • during operation                                       | -25 ... +85 °C  |
| • during storage   | -40 ... +90 °C  |
| <b>explosion protection category for dust</b>            | none  |
| <b>Installation/ mounting/ dimensions</b>                |   |
| <b>mounting position</b>                                 | any   |
| <b>fastening method</b>                                  | screw fixing  |
| <b>Certificates/ approvals</b>                           |   |
| General Product Approval                                 |   |



[Confirmation](#)



|                                       |                           |                   |       |
|---------------------------------------|---------------------------|-------------------|-------|
| Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates | other |
|---------------------------------------|---------------------------|-------------------|-------|

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE5112-0CH82>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE5112-0CH82>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SE5112-0CH82>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE5112-0CH82&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE5112-0CH82&lang=en)

last modified:

1/26/2022 