

2-Port DisplayPort to VGA Hub, DP1.2, TAA

MODEL NUMBER: B157-002-VGA











Converts and splits a DisplayPort video signal for display on two VGA monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

Description

The B157-002-VGA 2-Port DisplayPort to VGA Splitter converts and splits a DisplayPort video signal for display on two VGA-enabled monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in DisplayPort cable that connects to the source. It lets you use your existing VGA displays instead of buying new DisplayPort monitors or docking stations.

The B157-002-VGA supports video resolutions up to 1080p @ 60 Hz (1920 x 1080), as well as HDCP, EDID and DDC. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays. The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

Features

Converts and Splits DisplayPort Signal to 2 VGA Displays Simultaneouslyldeal for offices, conference rooms, trade shows and classroomsBuilt-in DisplayPort cable connects to sourceIncluded USB Micro-B cable supplies power to splitterSave money on new DisplayPort displays or docking stations

Top-Shelf PerformanceSupports video resolutions up to 1080p @ 60 Hz (1920 x 1080)Complies with HDCP, EDID and DDCLEDs indicate whether splitter is powered on and transmitting signal to connected displays

Easy to Use Almost AnywhereWorks with all operating systemsPlug and play—no software, drivers or external power supply requiredCompact unit fits easily in backpack or computer bag

Specifications

OVERVIEW	
UPC Code	037332191496
Product Type	Splitter

Highlights

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

Package Includes

- B157-002-VGA 2-Port DisplayPort to VGA Splitter
- USB Micro-B cable, 3 ft.
- · Owner's manual



Technology	VGA/SVGA; DisplayPort	
Host Connector	DISPLAYPORT (FEMALE)	
VIDEO		
Max Supported Video Resolution	1920 x 1080 (1080p) @ 60Hz	
Max Supported Color Depth	24-bit True Color	
3D Video Supported	Yes	
AUDIO		
Audio Specification	2.0-channel surround sound audio	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	(x2) Orange (Monitor Signal)	
PHYCICAL		
PHYSICAL Color	Black	
Material of Construction		
	Metal	
Wire Gauge (AWG)	28	
Cable Length (ft.)		
Cable Length (m)	0.00	
Shipping Dimensions (hwd / in.)	1.70 x 7.90 x 5.60	
Shipping Dimensions (hwd / cm)	4.32 x 20.07 x 14.22	
Shipping Weight (lbs.)	0.60	
Shipping Weight (kg)	0.27	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Dimensions (hwd / cm)	2.55 x 6.15 x 7.6	
Unit Dimensions (hwd / mm)	25.5 x 61.5 x 76	
Unit Weight (lbs.)	0.154	
Unit Weight (kg)	0.07	
COMMUNICATIONS		
EDID Compatible	Yes	
CONNECTIONS		
Number of Ports	2	
Side A - Connector 1	DISPLAYPORT (MALE)	
Side A - Connector 2	MICRO-USB B (FEMALE)	



	-	
Side B - Connector 1	(2) HD15 (FEMALE)	
Connector Plating	Nickel	
Input x Output	1 x 2	
Daisy-chainable / Cascadable	No	
FEATURES & SPECIFICATIONS		
MST Support	No	
Displayport Specification	1.2	
HDCP Specification	1.3	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.