

4


3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	L	REVISED PER ECO-15-015757	03NOV2016	RS	DR
	M	REVISED PER ECO-17-006294	10OCT2017	RS	DR
	N	REVISED PER ECO-18-000334	09JAN2018	RS	DR



- USE FOR AN UNSTRIPPED (SINGLE) WIRE END ONLY.
- WIRE INSUL DIA 3.810-5.334 [.150-.210].

1000	LOOSE PIECE	324696
QTY	PACKAGE TYPE	PART NO

AMP INCORPORATED CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE: 105° C [221° F]	THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L OLMEDA 14FEB95	TE Connectivity			
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752	VOLTAGE RATING: -	DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK M ELLIS 14FEB95				NAME T MICHIELUTTI
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111	CIRCULAR MIL AREA: -		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.127[.005] 4 PLC ± - ± - ANGLES	APVD T MICHIELUTTI 14FEB95	APPLICATION SPEC			
FOR ORDER ENTRY	1-800-526-5142	MATERIAL BODY, CU PER ASTM B152 INSUL, NYLON		FINISH BODY, TIN PLATE PER ASTM B545 INSULATION COLOR-YELLOW	WEIGHT -	SIZE A3	CAGE CODE 00779	DRAWING NO C-324696	RESTRICTED TO -
CUSTOMER DRAWING					SCALE 8:1	SHEET 1 of 1	REV N		