








### **RoHS Compliant**



# CC-525/CC-530 PCI 2xRS422/485 18MBaud

### "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



**brain**boxes

#### **Features**

- 2 port RS422/485
- PCI 2.3
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 18,000,000 18 MegaBaud Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**



PCI 2xRS422/485 18MBaud

CC-530 PCI 2xRS422/485 15MBaud



#### Description

This PCI card can run at an amazing speed of up to 18,000,000 baud. It provides 2 industry standard RS422/485 serial ports for PC compatibles in a single PCI slot. The card has on-board zener diodes giving transient spike protection to the inputs - making it ideal for factory automation installations. Includes drivers for all Windows 32 bit and 64 bit Operating Systems, including Windows 7.


Stunning ULTRA 15 or 18 megabaud data transfer rates!! And 128 byte deep FIFO guarantees uncompromising performance and fault free use.

With Brainboxes industry renowned Lifetime Warranty and 3 year Support!

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2003 32 bit 64 bit Editions
- Windows XP 32 bit 64 bit editions
- Windows 2000









ORDER

Description

PCI 2xRS422/485 18MBaud PCI 2xRS422/485 15MBaud

Code CC-525

CC-530

www.brainboxes.com



## PCI 2xRS422/485 18MBaud

#### CC-525/CC-530Full Specification

CC-323/CC-3301 dil 3pecil	ication	
Port	Ports	2 x RS422/485
Pin 1   TXD-   RS422/485 Pinout (9 Pin)	Connector	DB9 Connector - 9 Pin Male
Pin 2 TXD+ Pin 3 RTS- Pin 1 Pin 5	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 RTS+ Pin 5 GND	Operating Distance	RS422/485 Standard 4000 ft : 1200 metres
Pin 6 RXD- Pin 7 RXD+ Pin 8 CTS Pin 6 Pin 9	Cable	No Cable; Integrated Connector
Pin 9 CTS+		
Port Settings	Baud Rate	18,000,000 18 MegaBaud
Ultra	Data Bits	5,6,7 or 8
<b>&gt; &gt; &gt;</b> >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions
		Windows Server 2008 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions
		Windows Server 2003 32 bit 64 bit Editions
PCI <sup>°</sup>		Windows XP 32 bit 64 bit Editions
		Microsoft Windows ME Microsoft Windows 2000
	BUS	PCI Ultra: Stunning ULTRA 15 or 18 megabaud data transfer rates!!
	503	And 128 byte deep FIFO guarantees uncompromising performance
		and fault free use.
Approvals	Industry Approvals	AEO C-TPAT Microsoft Certified Gold Partner EMC: CE TAA
	Microsoft Approvals	Windows Server 2003 32 bit 64 bit editions
		Windows XP 32 bit 64 bit editions Windows 2000
	DCD I	
General	PCB Layers	4
	Power Consumption	360mA @ 5V
	Weight	0.091 kg
	Size	135l x 18w x 120h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCI 2xRS422/485 18MBaud
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
SETTING SETTING	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
WARD TO THE REAL PROPERTY OF THE PARTY OF TH		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Additional	<u> </u>	
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
Made in the UK		users. More Info: sales@brainboxes.com
Made in the UK		users. More Into: sales@brainboxes.com

Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial