



Screw-Screwless Connectors

900-07 RZ/ 2

terminal block, 2 pole, fixing: catch pin, clamping units per pole: 2, voltage rating: 450 V, current rating: 17.5 A, cross-section external: 2.5 mm², cross-section internal: 1.5 mm²



Order Info

reference number (ref.no.)	114802
PU	250
EAN	4028012104871

Type

type	terminal block
number of poles	2 pole
clamping units per pole	2
colour	white
cross-section rating	1.5 / 2.5 mm ²
connection type	screw-screwless

Technical Data

voltage rating	450 V
current rating	17.5 A
insulating material	PA
contact material	Spring Steel, Steel
flammability rating	V-2
max. ambient temperature operation	85 °C
assembly contact screw	0,8x4,0 / \cup 0,5 Nm
wall thickness min.	0.5 mm
wall thickness max.	1.4 mm
internal core cross-section min.	0.5 mm ²
internal core cross-section max.	2.5 mm ²
internal stripping length	7.0-7.5 mm
external stripping length	8.0-8.5 mm
fixing	catch pin
type of conductor solid external	yes
type of conductor flexible external	yes
type of conductor solid internal	yes
type of conductor stranded internal	yes
cross-section external	2.5 mm ²

cross-section internal	1.5 mm ²
-------------------------------	---------------------

Approvals

acc. to EN 60998	Download PDF
-------------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------

acc. to CSA	Download PDF
--------------------	------------------------------

Accessories

ZEL 110	196420
----------------	--------
