

# Han TC70 female contact 10mm<sup>2</sup>



Part number	09 11 000 6231
Specification	Han TC70 female contact 10mm <sup>2</sup>
HARTING eCatalogue	https://b2b.harting.com/09110006231

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Contacts
Series	TC 70
Type of contact	Crimp contact

## Version

Gender	Female
Manufacturing process	Turned contacts

## **Technical characteristics**

Conductor cross-section	10 mm <sup>2</sup>
Operating current	≤70 A
Contact resistance	≤0.5 mΩ
Stripping length	15.5 mm
Limiting temperature	-40 +125 °C
Mating cycles	≥500

#### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50

Page 1 / 2 | Creation date 2023-05-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 11 000 6231 Han TC70 female contact 10mm<sup>2</sup>



## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984

# Commercial data

Packaging size	10
Net weight	7 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140015418
eCl@ss	27440204 Contact for industrial connectors