



Material  
 Contact Pin: Brass  
 Insulator (housing): Thermoplastic (UL94V-0), Green  
 Surface of solder tail: Tin plated  
 Electrical cULus / VDE  
 Voltage rating: 300VAC / 300VAC  
 Current rating: 8A / 10A  
 Wire range:  
 Solid wire(AWG):  
 Wire strip length:  
 Withstanding Voltage: 1.6KV / 2.5KV  
 Operating temperature: -30°C to +105°C  
 Soldering temperature: 250°C±10°C/5 Sec  
 Safety Approval:

N= NUMBER OF CONTACTS

**RoHS compliant**

Unit:mm



File No.: E349947

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	10.12.2009	Dean
X.	±0.50					Approved	01.04.2016	Joanna
X.X	±0.30							
X.XX	±0.10							
DIM	TOL	②	Add UL	01.04.2016	Joanna			ASSMANN WSW-No. <b>A-TB381-VKxx</b>
X.°	±1°	①	Drawn	10.12.2009	Dean			Drawing-No. <b>ASS 3840 CO</b>
Angle	TOL	Id.	Modification	Date	Name	Replace		Sheet

1

2

3

4

5

6

7