Product data sheet Characteristics

VLSFH1UL

Disconnect switch, TeSys VLS, CC fuse holder, for 3 pole disconnect switch, for up to 25A fuse

Product availability: Stock - Normally stocked in distribution facility

Price*: 42.38 USD



Main

Range	TeSys	
Product name	TeSys VARIO LS	
Device short name	VLSFH	
Fuse size	CC	
Product or Component Type	Fuse holder	
Poles description	3P	
Network type	AC	

Complementary

Network Frequency	50/60 Hz
Mounting Support	DIN rail
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ith] conventional free air thermal current	25 A 131 °F (55 °C)
Connections - terminals	Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.02 in ² (16 mm ²) flexible without cable end
Tightening torque	Power circuit 15.9317.70 lbf.in (1.82 N.m) screw clamp terminals
Height	2.96 In (75.2 mm)
Width	2.07 In (52.5 mm)
Depth	3.15 ln (80.1 mm)
Net Weight	0.30 Lb(US) (0.135 kg)

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3
Product Certifications	CULus GL
IP degree of protection	IP20 IEC 60529
Ambient air temperature for operation	-13131 °F (-2555 °C)

Ordering and shipping details

Category	21734-TESYS VLS DISCONNECT SWITCHES
Discount Schedule	CP1
GTIN	3606481157140
Returnability	Yes
Country of origin	IT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.56 ln (6.5 cm)
Package 1 Width	3.54 ln (9.0 cm)
Package 1 Length	3.82 ln (9.7 cm)
Package 1 Weight	4.76 Oz (135.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	5.91 ln (15.0 cm)
Package 2 Width	11.81 ln (30.0 cm)
Package 2 Length	15.75 ln (40.0 cm)
Package 2 Weight	6.05 Lb(US) (2.746 kg)

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	€Yes	

Product Life Status : Commercialised