



Product: <u>633938</u> ☑

Surveillance CATV MATV, RG-6 #18 Sol BC, FFEP Core, Duofoil® + AL Braid, Flamarrest® Jkt, CMP, CATVP

Product Description

Surveillance, CATV & MATV, RG6, 18 AWG solid bare copper, foam FEP core, Duofoil® + 90% aluminum braid, Low Smoke PVC jacket, CMP & CATVP

Technical Specifications

Product Overview

Suitable A	Suitable Applications: CATV, MATV			
Construction Details				
RG Type: 6				
Conducto	or			
Size	Stranding	Nom. Diameter	Material	
18 AWG	Solid	0.040 in	BC - Bare Copper	
Insulation	1			

Material	Nom. Insulation Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	0.170 in (4.32 mm)

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Таре	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
2	Braid	Aluminum		90%

Outer Jacket

	Material	Nom. Diameter
I	PVC - Polyvinyl Chloride	0.233 in (5.92 mm)
(Overall Cable Diameter (N	Nominal): 0.233 in (5

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
6.4 Ohm/1000ft (21 Ohm/km)	3.5 Ohm/1000ft (11 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	83%

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Installation Min.

Max. Pull Tension:	76 lbs (34 kg)
Bulk Cable Weight:	27 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor			
Sustainability:	CA Prop 65, Product Lens™, Environmental Product Declaration (EPD) Available			
Flammability / Reaction to Fire:	NFPA 262			
NEC / UL Compliance:	CATVPCMP			
CEC / C(UL) Compliance:	CMP			
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

History

Part Numbers

Variants

	Item #	Color	Putup Type	Length	UPC
6	33938 010U1000	Black	UnReel	1,000 ft	612825176091
6	33938 008U1000	Gray	UnReel	1,000 ft	612825176077
6	33938 877500	Natural	Reel	500 ft	612825176121
6	33938 8771000	Natural	Reel	1,000 ft	612825176114
6	33938 877U1000	Natural	UnReel	1,000 ft	612825176107
6	33938 009U1000	White	UnReel	1,000 ft	612825176084

© 2023 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.