



Screw Terminal Blocks

2000/ 2 DS

terminal block, 2 pole, insulating material: PA, cross-section rating: 16.0 mm², pin spacing: 14.50 mm, mounting hole diameter: 4.3 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 76 A



Order Info

| | |
|----------------------------|---------------|
| reference number (ref.no.) | 128302 |
| PU | 120 |
| EAN | 4028012106530 |

Type

| | |
|-------------------------|----------------------|
| type | terminal block |
| number of poles | 2 pole |
| clamping units per pole | 1 |
| colour | natural |
| cross-section rating | 16.0 mm ² |
| connection type | screw |
| wire protector (DS) | yes |

Technical Data

| | |
|------------------------------------|----------------------|
| voltage rating | 500 V |
| current rating | 76 A |
| insulating material | PA |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 10.0 mm ² |
| flammability rating | V-2 |
| min. ambient temperature | -40 °C |
| max. ambient temperature operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 10.0-10.5 mm |
| assembly contact screw | 1,0x5,5 / ⚙ 2,0 Nm |
| mounting hole diameter | 4.3 mm |
| pin spacing | 14.50 mm |
| fixing | screw |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 60998 | Download PDF |
| acc. to UL | Download PDF |
| acc. to CSA | Download PDF |

Accessories

| | |
|-------------------|--------|
| 2000 BZ/ 2 | 191802 |
| ZEL 110 | 196420 |