

## Temperature, humidity, pressure regulator with two relay and RS485 outputs

code: H7430



Humidity, temperature, atmospheric pressure transmitter with two relay outputs. Outdoor, indoor use.  
Built-in relative humidity, temperature, pressure sensors. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy. Three two-state inputs.

### Technical data

<b>TEMPERATURE SENSOR</b>	
Measuring range	-30 to +80 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
<b>HUMIDITY SENSOR</b>	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
<b>DEW POINT</b>	
Measuring range	-60 to +80 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
<b>ATMOSPHERIC PRESSURE SENSOR</b>	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
<b>RELAY OUTPUTS</b>	
Quantity	2
Maximal voltage	50 V
Maximal current	2 A
Maximal power	60 VA
<b>BINARY INPUTS</b>	
Quantity	3
Signal for binary input	dry contact, open collector or two-state voltage signal. Inputs are not galvanically isolated.
Minimum pulse duration on binary input	500 ms
Voltage across open contact	< 3,3 V
Low voltage level	0 to +0,5 V

High voltage level	+3,0 to +30 V
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	internal sensor of temperature, humidity sensor and atmospheric pressure
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Acoustic alarm	from built-in beeper - switchable
Output	RS485
Range of humidity sensor temperature compensation	all temperature range
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	ModBus RTU, ARION, Advantech ADAM
Power	9-30 Vdc
Protection class	IP54 electronics; IP40 sensors
Dimensions	136 x 213 x 45 mm; stem length 75 mm
Weight	approx. 360 g
Warranty	3 years