

Specification Sheet

Part Number: 596-00255

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

MAIN PHOTOVOLTAIC SYSTEM AC DISCONNECT Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Reflective, MAIN PV AC DISCONNECT, 5.5" x 1.75", VL, Red, 50/roll

Article Number 596-00255

Type MPVACDIS

Color Red (RD)

Quantity Per roll

Product Description HellermannTyton Pre-Printed Solar Installation Labels are designed

to meet the requirements of the National Electrical Code® (NEC®) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder-coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Reflective, MAIN PV AC DISCONNECT, 5.5" x 1.75", VL, Red, 50/roll
Global Part Name	MPVACDIS-505/281-RD
Local Order Number 2	Cross Reference = 10 per pack: 596-00676; Metal Solar Placard 5 pack: 596-00861
Width W (Imperial)	5.5
Width W (Metric)	139.7
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.75
Height H (Metric)	44.40
Material	Type 505/281, UV-stabilised, reflective vinyl with clear polyester laminate (505/281)
Material Shortcut	505/281
Adhesive	Acrylic
Halogen Free	No

UV Resistant (Yes/No) Yes Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification UL 969 NEC2011 IFC 2012 NEC2017 NEC2020 NEC2023 Warranty (US) Yes UL Recognized (US) Yes Package Quantity (Imperial) 50 Package Quantity (Metric) 50 **Customs Number** 3919102055

Labels per Column

Labels per Row

1

1