


注)
NOTES:

- 材質
MATERIAL
銅合金 (板厚: 0.3)
COPPER ALLOY (THICKNESS: 0.3)
- メッキ仕様
TERMINAL PLATING
接点部 : 金メッキ 0.25 μm MIN.
CONTACT AREA : GOLD 0.25 MICROMETER MIN.
圧着部 : 錫メッキ 1.0 μm MIN.
CRIMP AREA : TIN 1.0 MICROMETER MIN.
下地メッキ : ニッケルメッキ 2.0 μm MIN.
UNDER PLATE : NICKEL 2.0 MICROMETER MIN.
- 適用電線範囲 : UL 2517 , AWG #16
APPLICABLE WIRE RANGE : UL2517 , AWG #16
- 被覆外径 : φ2.2~φ2.7
INSULATION EXTERNAL DIA : φ2.2~φ2.7
- 適用ハウジングアッセンブリ : 51195 シリーズ
APPLICABLE HOUSING ASS'Y : 51195 SERIES
- 本製品は59319-**-90の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 59319-**-90.



連鎖状 CHAIN	59319-0028	59319-**-28
端子形状 TERMINAL CONFIGURATION	MATERIAL No.	MODEL No.

DIMENSIONS: SHT REV

MATERIAL 材料	—#—	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	10 UNDER 未満	±0.2	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. DIMENSION UNITS: mm SCALE: 1:1 GENERAL TOLERANCES (UNLESS SPECIFIED): 4 PLACES ± 0.15 mm / ± 0.006 in. 3 PLACES ± 0.20 mm / ± 0.008 in. 2 PLACES ± 0.25 mm / ± 0.010 in. 1 PLACE ± 0.30 mm / ± 0.012 in. 0 PLACES ± 0.35 mm / ± 0.014 in. ANGULAR TOL: ± 0.5° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS THIRD ANGLE PROJECTION EC NO: 638770 DRWN: VLOKESHA 2020/03/12 CHK'D: GGA 2020/07/21 APPR: GGA 2020/07/21 INITIAL REVISION: DRWN: Y.WADA 2004/03/29 APPR: M.SASAO 2004/03/29 CURRENT REV DESC: OBSOLETE PART NUMBER molex POWER REC CRIMP TERM -LEAD FREE- PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: SD-59319-002 DOC TYPE: PSD DOC PART: 001 REVISION: A MATERIAL NUMBER: SEE CHART CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 1
FINISH 仕上げ	—#—		10 OVER 30 UNDER 以上 未満	±0.25	
WIRE RANGE 適用電線範囲	—#—		30 OVER 以上	±0.3	
INS. RANGE 被覆外径	—#—	ANGLE 角度		±3°	