



PART NUMBER CHART			
COLOR	PART NUMBER		
GREY	ATM6S-BT		
BLACK	ATM6S-BT-BK		
YELLOW	ATM6S-BT-YW		

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. THIS PART IS USED ON ATM06-6S PLUG WITH ANY MODIFICTION THAT DOES NOT INCLUDE AN END CAP.
- 2. TEMPERATURE RATING: -29°C TO +100°C [-20°F TO +212°F]
- 3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	SEE PART NUMBER CHART		REF	REF: DTM6S-BT, DTM6S-BT-BK, STM6S-BT-YW		
	PART NUMBER			DESCRIPTION		
QUANTITY MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED		SIGNATUR	ES DATE	A manhanal		
1) All dimensions a 2) Tolerances are a 1 PL DEC ±0.30		DRAWN: BROOK.DII	NG 13MAR20	<ul><li>Amphenol</li></ul>		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED: ORION.L	16MAR20	Sine Systems - www.amphenol-sine.com		
3) Note reference	- <u>x</u>	ENGINEER:		44724 Morley Drive		
MATERIAL SPECIFICA	TIONS:	APPROVAL: TOMMY.X	E 17MAR20	Clinton Township, MI 48036		
PVC  THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES SPECIFICATIONS:  PROCESS SPECIFICATIONS:  SPECIFICATIONS AND PERFORMANCE D SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO ING OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL DIMENSIONS ARE SUBJECT TO NORMAL		CUSTOMER:		BOOT .ATM .6 WAY .PLUG		
		HE PROPERTY OF RATION, NO RIGHTS IMPLIED, ALL	ATM6S-BT-XX	A1		
NEXT ASS'Y:		MANUFACTURING VARIA		SCALE: NONE SHEET 1 C	F 1	