

Pneumatic contact fem. with valve 3,0 mm



Part number	09 14 000 6257
Specification	Pneumatic contact fem. with valve 3,0 mm
HARTING eCatalogue	https://b2b.harting.com/09140006257

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Type of contact	Pneumatic contact
Description of the contact	With shut-off Polypropylen Straight
Version	
Gender	Female
Manufacturing process	Turned contacts
Technical characteristics	
Limiting temperature	-40 +80 °C
Operating pressure	≤8 bar
Tube inner diameter	3 mm
Material properties	
Material (contacts)	Delrin acetal
Material (seal)	Buna-N
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained

Page 1 / 2 | Creation date 2023-05-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



REACH SVHC substances	Not contained
Specifications and approvals	
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Commercial data	
Packaging size	10
Net weight	0.9 g
Country of origin	Germany
European customs tariff number	39269097
GTIN	5713140018419
eCl@ss	27440204 Contact for industrial connectors