



Circular Connectors IP68  
Circular Connectors AC 167 micro  
**AC 167 REST/2 M16**



panel mount plug, 2 pole, voltage rating: 500 V, current rating: 10 A

### Order Info

reference number (ref.no.)	72876216
PU	200
EAN	4028012133833

### Type

type	panel mount plug
number of poles	2 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	1.0 mm <sup>2</sup>
connection type	screw
protection against incorrect plugging	yes
latch	yes

### Technical Data

voltage rating	500 V
current rating	10 A
impulse voltage rating	4.0 kV
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.25 mm <sup>2</sup>
core cross-section max.	1.0 mm <sup>2</sup>
protection class	SK II
flammability rating	V-0
max. ambient temperature operation	60 °C
IP code	IP66/IP68/IP69
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0 mm
dismantling length	20.0 mm

<b>assembly contact screw</b>	M2 - max. $\tau$ 0,2 Nm
<b>wall thickness max.</b>	7.0 mm
<b>housing hole diameter</b>	M16
<b>tightening torque lock nut</b>	1,5 Nm

## Accessories

<b>AC 167 RVKS M16</b>	729042
<b>AC 167 RWZ/2</b>	729044