

## Specification Sheet

Part Number: 596-00816

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC® code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

VOLTAJE NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
FRECUENCIA NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
POTENCIA MÁXIMA DE CA	<input type="text"/>
CORRIENTE MÁXIMA DE CA	<input type="text"/>
SOBRECORRIENTE NOMINAL MÁXIMA DEL DISPOSITIVO PARA PROTECCIÓN DEL MODULO DE CA	<input type="text"/>

Solar Label, Printable, Spanish, AC Module, 4.0" x 2.0", PET, Red, 50/roll

Article Number 596-00816

Type AC2011S

Color Red (RD)

Quantity Per roll

**Product Description** Designed with cross-laminated UV stable materials, these variable print Solar Installation Labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

Short Description	Solar Label, Printable, Spanish, AC Module, 4.0" x 2.0", PET, Red, 50/roll
Global Part Name	AC2011S-840/281-RD
Local Order Number 2	English Version: 596-00252
Width W (Imperial)	4.0
Width W (Metric)	101.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Material	Type 840/281, Polyester, UV-stabilised, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen Free	Yes
UV Resistant (Yes/No)	Yes

Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	CSA 66956
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1