



## Building Installation Connector System AC 166®

G

### Plug and Socket Connectors Flat Version

## AC 166 GSTF/515 WS

plug, connection type: screw, 5 pole, white, coding: 1 (mains), cable diameter min.: 9.3 mm, cable diameter max.: 10.3 mm, voltage rating: 400 V, current rating: 20 A, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

<b>reference number (ref.no.)</b>	162455
<b>PU</b>	100
<b>EAN</b>	4028012106981

### Type

<b>type</b>	plug
<b>number of poles</b>	5 pole
<b>clamping units per pole</b>	1
<b>colour</b>	white
<b>coding</b>	1 (mains)
<b>cross-section rating</b>	2.5 mm <sup>2</sup>
<b>connection type</b>	screw
<b>PE function</b>	yes
<b>protection against incorrect plugging</b>	yes

### Technical Data

<b>voltage rating</b>	400 V
<b>current rating</b>	20 A
<b>impulse voltage rating</b>	4.0 kV
<b>insulating material</b>	PA
<b>contact material</b>	brass
<b>core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>core cross-section max.</b>	4.0 mm <sup>2</sup>
<b>flammability rating</b>	V-2
<b>max. ambient temperature operation</b>	70 °C
<b>IP code</b>	IP20
<b>IP code when plugged</b>	IP40
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes

<b>stripping length</b>	7.0 mm
<b>dismantling length PE</b>	39.0 mm
<b>dismantling length</b>	32.0 mm
<b>assembly contact screw</b>	0,5x3,0 / $\cup$ 0,3 Nm
<b>assembly strain relief</b>	PZ 1 / $\cup$ 0.5 Nm
<b>cable diameter min.</b>	9.3 mm
<b>cable diameter max.</b>	10.3 mm
<b>strain relief</b>	yes

## Approvals

<b>acc. to EN 61535</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>AC 166 VSF SW</b>	169563
<b>AC 166 VSF WS</b>	169553