




## UDSK32-7/8"-22MM-F

Ruland UDSK32-7/8"-22MM-F, 7/8" x 22mm Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.995" (50.7mm) OD, 8.688" (220.7mm) Length





## **Description**

Ruland UDSK32-7/8"-22MM-F is a double cardan friction bearing universal joint with 0.8750" x 22mm bores, 3/16" x 6mm keyways, 1.995" (50.7mm) OD, 8.688" (220.7mm) length, and 3/8-16 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK32-7/8"-22MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT32/51-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

**Product Specifications** 

| Keyway (K1)         3/16 in         Keyway (K2)         6 mm           B1 Max Shaft Penetration         1.700 in (43.2 mm)         B2 Max Shaft Penetration         1.700 in (43.2 mm)           Joint Outer Diameter (OD)         1.995 in (50.7 mm)         Bore Tolerance         +0.0010 in / -0.0000 in (+0.025 m / -0.000 mm)           Length (L)         8.688 in (220.7 mm)         Center Yoke Length (LC)         3.188 in (81.0 mm)           Yoke Length (LY)         2.750 in (69.9 mm)         Hub Depth (LH)         1.700 in (43.2 mm)           Broached Set Screw         3/8-16         Screw Finish         Black Oxide           Peak Torque         19,350 in-lb (2,186.3 Nm)         Rated Torque         3,870 in-lb (437.3 Nm)           Max Operating Angle         90°         Material Specification         Alloy Steel           Manufacturer         Belden Universal         Country of Origin         USA           Recommended Lubricant         LUBRIPLATE No. 1200-2         Matching Boot Cover         UBOOT32/51-NI-KIT           UPC         63452932807         Tariff Code         8483.60.4000           UNSPC         25173810           Note 1         Performance ratings are for guidance only. The user must determine suitability for a particular application. | Product Specifications          |  |                                 |  |
|---|---------------------------------|--|---------------------------------|--|
| B1 Max Shaft Penetration Joint Outer Diameter (OD)  1.995 in (50.7 mm)  Bore Tolerance  +0.0010 in /-0.0000 in (+0.025 m /-0.000 mm)  Length (L)  8.688 in (220.7 mm)  Center Yoke Length (LC)  3.188 in (81.0 mm)  Yoke Length (LY)  2.750 in (69.9 mm)  Hub Depth (LH)  1.700 in (43.2 mm)  Broached Set Screw  3/8-16  Screw Finish  Black Oxide  Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Bore (B1)                       | 0.8750 in  | Small Bore (B2)                 | 22 mm  |
| Joint Outer Diameter (OD)  1.995 in (50.7 mm)  Bore Tolerance  +0.0010 in / -0.0000 in (+0.025 m / -0.000 mm)  Length (L)  8.688 in (220.7 mm)  Center Yoke Length (LC)  3.188 in (81.0 mm)  Yoke Length (LY)  2.750 in (69.9 mm)  Hub Depth (LH)  1.700 in (43.2 mm)  Broached Set Screw  3/8-16  Screw Finish  Black Oxide  Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Keyway (K1)                     | 3/16 in  | Keyway (K2)                     | 6 mm   |
| Length (L)  8.688 in (220.7 mm)  Center Yoke Length (LC)  3.188 in (81.0 mm)  Yoke Length (LY)  2.750 in (69.9 mm)  Hub Depth (LH)  1.700 in (43.2 mm)  Broached Set Screw  3/8-16  Screw Finish  Black Oxide  Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | <b>B1 Max Shaft Penetration</b> | 1.700 in (43.2 mm)   | <b>B2 Max Shaft Penetration</b> | 1.700 in (43.2 mm)                                 |
| Yoke Length (LY)  2.750 in (69.9 mm)  Hub Depth (LH)  1.700 in (43.2 mm)  Broached Set Screw  3/8-16  Screw Finish  Black Oxide  Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  Note 1  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Joint Outer Diameter (OD)       | 1.995 in (50.7 mm)   | Bore Tolerance                  | +0.0010 in / -0.0000 in (+0.025 mm<br>/ -0.000 mm) |
| Broached Set Screw  3/8-16  Screw Finish  Black Oxide  Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Length (L)                      | 8.688 in (220.7 mm)  | Center Yoke Length (LC)         | 3.188 in (81.0 mm)                                 |
| Peak Torque  19,350 in-lb (2,186.3 Nm)  Rated Torque  3,870 in-lb (437.3 Nm)  Max Operating Angle  90°  Material Specification  Alloy Steel  Manufacturer  Belden Universal  Country of Origin  USA  Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  UPC  63452932807  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Yoke Length (LY)                | 2.750 in (69.9 mm)   | Hub Depth (LH)                  | 1.700 in (43.2 mm)                                 |
| Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT32/51-NI-KITUPC63452932807Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application.Prop 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Broached Set Screw              | 3/8-16   | Screw Finish                    | Black Oxide  |
| Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT32/51-NI-KIT UPC 63452932807 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application. Prop 65  MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Peak Torque                     | 19,350 in-lb (2,186.3 Nm)  | Rated Torque                    | 3,870 in-lb (437.3 Nm)                             |
| Recommended Lubricant  LUBRIPLATE No. 1200-2  Matching Boot Cover  UBOOT32/51-NI-KIT  63452932807  Tariff Code  8483.60.4000  UNSPC  25173810  Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Max Operating Angle             | 90°  | Material Specification          | Alloy Steel  |
| UPC 63452932807 Tariff Code 8483.60.4000  UNSPC 25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | Manufacturer                    | Belden Universal   | Country of Origin               | USA  |
| UNSPC  25173810  Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to  | Recommended Lubricant           | LUBRIPLATE No. 1200-2  | Matching Boot Cover             | UBOOT32/51-NI-KIT                                  |
| Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.  Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | UPC                             | 63452932807  | Tariff Code                     | 8483.60.4000                                       |
| Prop 65  WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to   | UNSPC                           | 25173810   |                                 |  |
| California to cause cancer and birth defects or other reproductive harm. For more information go to   | Note 1                          | Performance ratings are for guidance only. The user must determine suitability for a particular application. |                                 |  |
|   | Prop 65                         | California to cause cancer and birth defects or other reproductive harm. For more information go to          |                                 |  |