



Building Installation Connector System AC 166®

G Panel Mounting

AC 166 GEBU/ 4 SW



panel mount socket, 4 pole, black, coding: 1 (mains), wall thickness min.: 0.5 mm, wall thickness max.: 1.2 mm, voltage rating: 400 V, current rating: 20 A, cross-section rating: 2.5 mm², connection type: screwless

Order Info

| | |
|-----------------------------------|---------------|
| reference number (ref.no.) | 168864 |
| PU | 150 |
| EAN | 4028012107568 |

Type

| | |
|--|---------------------|
| type | panel mount socket |
| number of poles | 4 pole |
| clamping units per pole | 2 |
| colour | black |
| coding | 1 (mains) |
| cross-section rating | 2.5 mm ² |
| connection type | screwless |
| PE function | yes |
| protection against incorrect plugging | yes |

Technical Data

| | |
|---|---------------------|
| voltage rating | 400 V |
| current rating | 20 A |
| impulse voltage rating | 4.0 kV |
| insulating material | PA |
| contact material | Spring Steel, Brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| flammability rating | V-2 |
| max. ambient temperature operation | 70 °C |
| IP code | IP20 |
| IP code when plugged | IP40 |
| type of conductor solid | yes |
| stripping length | 8.0-9.0 mm |

| | |
|----------------------------|------------|
| wall thickness min. | 0.5 mm |
| wall thickness max. | 1.2 mm |
| fixing | catch wing |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 61535 | Download PDF |
| acc. to UL | Download PDF |
| acc. to CSA | Download PDF |

Accessories

| | |
|----------------------|--------|
| AC 166 VSE SW | 169463 |
| AC 166 VSE WS | 169453 |