

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDITY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : $\phi 8.8 \pm 0.5$
<b>SPECIFICATIONS</b>				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK  Unless otherwise specified, refer to JIS C 5402.		APPROVED	A0. SUZUKI	09. 10. 05
		CHECKED	KN. ICHIKAWA	09. 10. 02
		DESIGNED	TU. TANIGUCHI	09. 10. 02
		DRAWN	TU. TANIGUCHI	09. 10. 02
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126659-00	
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH-37-CMB (8. 8)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0033-0-00	1/