SIEMENS

Data sheet US2:HF362JCH



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. 60A 3P 600V FUSED RECEPT SW TYPE 12

mechanical service life (switching cycles) typical	10000
fastening method	SURFACE
number of poles	3
suitability for operation	PROTECTION OF HEAVY DUTY PORTABLE EQUIPMENT
Electricity	
ampacity	60 A
supply voltage frequency rated value 50/60 Hz	Yes
Environmental conditions	
ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C
Model	
product brand name	SIEMENS
product brand name product sub brand name	SIEMENS VBII
· .	
product sub brand name	VBII
product sub brand name product type designation	VBII HEAVY DUTY SWITCH
product sub brand name product type designation special product feature	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS
product sub brand name product type designation special product feature type of electrical connection	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS
product sub brand name product type designation special product feature type of electrical connection Mechanical Design	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS INTERLOCKED PLUG
product sub brand name product type designation special product feature type of electrical connection Mechanical Design design of the housing	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS INTERLOCKED PLUG TYPE 12
product sub brand name product type designation special product feature type of electrical connection Mechanical Design design of the housing design of the actuating element	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS INTERLOCKED PLUG TYPE 12 SINGLE THROW
product sub brand name product type designation special product feature type of electrical connection Mechanical Design design of the housing design of the actuating element material	VBII HEAVY DUTY SWITCH ACCEPTS CROUSE-HINDS Arktite PLUGS INTERLOCKED PLUG TYPE 12 SINGLE THROW

last modified: 9/15/2021 🖸