ATGBICS

ATGBICS JL563A HP Aruba Compatible Transceiver SFP+ 10G Base T (RJ45, Copper, 30m)

Brand : ATGBICS

Product name : JL563A HP Aruba Compatible Transceiver SFP+ 10G Base T (RJ45, Copper, 30m)

Product code: JL563A-C

JL563A HP Aruba Compatible Transceiver SFP+ 10G Base T (RJ45, Copper, 30m)

ATGBICS JL563A HP Aruba Compatible Transceiver SFP+ 10G Base T (RJ45, Copper, 30m):

ATGBICS JL563A 10GBase-T supports a distance of up to 30m over a copper connection via a RJ-45 connector. It is specifically designed for high speed communication links that require 10 Gigabit Ethernet over Cat 6a/7. Our product meets the specification of HP Aruba JL563A= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.
ATGBICS JL563A HP Aruba Compatible Transceiver SFP+ 10G Base T (RJ45, Copper, 30m). SFP transceiver type: Copper, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 2.5 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

Performance

SFP transceiver type *	Copper
Maximum data transfer rate *	10000 Mbit/s
Interface type *	SFP+
Single-mode fiber (SMF) supported	✘
Multi-mode fiber (MMF) supported	✘
SFP transceiver standard	TX
Maximum transfer distance	30 m
Ethernet LAN	✔
Ethernet interface type	10 Gigabit Ethernet
Copper ethernet cabling technology	10GBASE-TX
Digital Diagnostics Monitoring (DDM)	✘

Features

Product colour	Silver
Housing material	Metal
Plug and Play	✔
Hot-Plug support	✔
Hot-swap	✔
Easy to install	✔
Country of origin	United Kingdom
Brand compatibility	Aruba Networks
Certification	CE, FCC, RoHS

Power

Input voltage	3.3 V
Maximum voltage	4 V
Power consumption (typical)	2.5 W

Operational conditions

Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	13.4 mm
Depth	56.6 mm
Height	8.5 mm
Weight	24 g

Packaging data

Number of products included	1 pc(s)
Package type	Box

Technical details

Sustainability compliance	✔
Sustainability certificates	RoHS
Doesn't contain	Lead

5056468711687