



Cross-connector, No. of poles: 4, Mounting type: Can be screwed on, Width: 98 mm, Rated cross-section: 120 mm², Colour: natural

Business data

Article number	17280.0
Article name	SQ 120/4
GTIN (EAN)	4044211189488
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	130.84 g
Weight per piece (including packaging)	131.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connector
Colour	Natural

Technical data

Dimensions

Length	10 mm
Width	98 mm
Height	27.5 mm
Hole diameter	5.5 mm
Hole spacing (mid-point to mid-point)	27 mm
Pitch size	27 mm

Ratings

Max. voltage	1000 V
Rated current	269 A
Current load, max.	290 A
Rated cross-section	120 mm ²
Contamination degree	3

Connection data

No. of poles	4
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	3.2 Nm
Tightening torque, max.	3.7 Nm

Materials

Material	Copper
Surface	Tin-plated
Surface screw	Galvanized

Further technical data

Mounting type	Screwable
Number of bridged terminals	4

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Media



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 120 mm², Width: 27 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17165.2</u>	SRK 120/2A BG	4044211189372	5



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 120 mm², Width: 27 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17165.2</u>	SRK 120/2A BG	4044211189372	5